

LD-LED150

Large Slave Display

SENSOR
TECHNIQUES LIMITED



Large Display, Model LD-LED150

- 5 digit display with sign
- Very bright 150mm high red LED digits
- Suitable for use with overhead crane weighers
- Legible from long distances
- Suitable for our Digital amplifiers and Indicators
- RS232 interface as standard, RS422 optional
- Robust sheet steel enclosure
- Power supply 115/230 VAC
- Dimensions : 971 x 228 x 123mm (W x H x D)
- Sealed to IP64




MAINS CONNECTOR



- 1 - LIVE
- 2 - Neutral
- 3 - N/C
- 4 - Earth


RS232 CONNECTOR



- A - Tx(out)
- B - Rx(in)
- C - Ground

D, E, F, G, H - No Connection

RS422 CONNECTOR



- D - Tx
- E - $\overline{\text{Tx}}$
- F - $\overline{\text{Rx}}$
- G - Rx
- H - Ground

A, B, C - No Connection

Specification

All Dimensions in mm
Specifications are subject to change without prior notice

Digit size	: 150mm
Number of digits	: 5 full digits plus sign
Display colour	: Red
Supply voltage	: 115VAC or 230VAC ($\pm 10\%$) 50/60Hz
Interface	: RS232 standard, RS422 optional
Baud rate	: 9600 baud
Protocol	: ASCII protocol. Display sends GN command to host instrument to Get Net weight Designed to work with any of our instrumentation which has a digital interface.
Temperature Range (Working)	: -10°C to +60°C
Temperature Range (Storage)	: -20°C to +85°C
Housing	: Metal case (IP64) with steel wall brackets
Dimensions	: 971 x 123 x 228 mm, Weight approximately. 8.5Kg

DS-LD-LED150-1, 09/03