



Large Crane Display 1700 Load Cell Indicator

Wall mounting swivel brackets...



...or simply panel mount !

INTRODUCTION

- Low cost, attractive styling
- Dual alarms included as standard
- Remotely Scalable
- Excitation supply included
- Universal power supply
- High noise immunity
- Wall or suspension mounting
- Units of measure label – free on request

Features

- Sealed to IP65 for 25mm, 57mm, 102mm, 144mm versions.
- Sealed to IP54 for 200mm and 280mm versions.
- All settings remotely adjustable via contact closures.
- Analogue input.



Procter & Chester Measurements

Specifications:

PARAMETER	
Power Supply	95 – 265VAC as standard.
Power Supply OPTION	11-30VDC
Power consumption	20Watts maximum
Alarm OPTION	2 alarms SPST rated 2A 250VAC. Selectable HI or LO. Display flashes in alarm state.
Mounting methods	Wall, panel, or suspension, mounting kit included.
Operating temperature	-10 to +50 DegC
Storage temperature	-40 to +60 DegC
Humidity	25-144mm types 100% (IP65) 200-280mm types 0-60% non condensing (IP54)

Additional Information

DIGIT SIZE – TOTAL OF 5 DIGITS	CASE DIMENSIONS- mm: (90mm DEPTH)	VIEWING DISTANCE
25MM	TBC	10m
57MM	288 x 120	20m
102MM	480 x 168	40m
144MM	624 x 192	60m
200MM	824 x 248	80m
280MM	1172 x 336	110m



NOTE:

The operator will require an additional amplifier between the load cell and large display.

CE Approved

Document Revision Date: 0505